

Meto MR-4/MI-4 Stand Alone

[The off-line answer
to printing]

The Meto MR-4/MI-4 Stand Alone is the best off-line thermal-printer of its kind. It is an ideal solution unit for retail stores, shipping and receiving warehouses, document tracking, and inventory needs.

Product Highlights

- Suitable for all Meto MR-4 and MI-4 printers with display.
- Create label layouts without ever using a PC.
- Save labels in printers memory.
- Recall and print labels on demand.
- Backup software included.
- High print speed.
- Easy to maintain printer.

No PC
required

Meto MR-4208



Meto MI-4208



Innovative Printing Systems

Printer Specifications

	Meto MR-4208*	Meto MI-4208*
print method	direct thermal / thermal transfer	
printhead-Technology	flathead type	
Resolution	203dpi	
Print Speed	200mm/s (8"/s)	
Print Width	108mm (4,25")	104mm (4,1")
Print Length	6mm - 2.475mm (0,25" - 99")	
Memory	8MB DRAM; 2MB Flash	8MB SDRAM; 1MB Flash
Controls	adjustable contrast LCD 5-button panel	
Cabinet	plastic; clear side window	metal; clear side window
Interfaces	USB; Centronics Parallel Port, serial DB9 RS232	Centronics Parallel Port, serial DB9 RS232
Dimensions (HxWxD)	26,2cm x 24,9cm x 45,9cm (10,3" x 9,8" x 18,06")	22,4cm x 24,1cm x 42,2cm (8,8" x 9,5" x 16,6")
Weight	12,2kg (27,0lbs)	20kg (45lbs)
Temperature/Humidity	4°C to 35°C	
Listings	UL, CSA, TÜV GS, FCC Class A; CE	

Printmedia Specifications

Media Type	Roll fed or fanfold materials; fanfold accepted from rear or bottom of printer	
Media Sensing	"See through" for liner backed die cut labels and tags; Reflective sensor for black mark media	
Media Width	25,4mm - 118mm (1" - 4,65")	
Media Thickness	0,635mm - 0,254mm (0,0025" - 0,1")	0,635mm - 0,254mm (0,0025" - 0,1")
Media Supply Roll Capacity	203mm (8") outer diameter on 40/76mm 1,5/3,0" core	
Ribbon Format	Industry standard ribbon widths; 450m (1.476") in length	Industry standard ribbon widths; 600m (1.968") in length
Ribbon Supply Roll	25mm core diameter (1")	
Ribbon Coating	inkside in	

Barcodes

1-D Codes	all popular 1D codes supported
2D-Codes	all popular 1D codes supported
Rotation	all barcodes can be printed in four directions: 0°, 90°, 180° and 360°

Fonts

Resident Fonts	Ten alphanumeric fonts from 0,9mm (0,03") to 6mm (0,25") including OCR A, OCR B, CG Triumvirate	Ten alphanumeric fonts from 0,89mm (0,03") to 16mm (0,64") including OCR A, OCR B, CG Triumvirate/Bold Condensed
Downloadable font types	True-Type, AGFA Intellifont, Bitmap	
Character Set	Modified IBM Codepage 850	
Font expansion/rotation	All fonts expandable vertically and horizontally up to 24x	
Graphics supported	PCX, BMP and IMG files	
Rotation	all fonts and graphics can be printed in four directions: 0°, 90°, 180° and 360°	

Options

	Thermal Transfer Kit
	Media Cutter
	Peel & Present mechanism (requires Internal rewind option)
	Internal Rewind
	Label Present Sensor
	External Ethernet Connectivity
	Flash Memory expansion
	Internal Ethernet Printserver
	MCL enabled
Metal Cover	RF-Net Internal 802.11b Wireless Ethernet
	USB Interface
	Twinax/Coax-Interface
	I/O Interface expansion card
	Linear Scanner (Read after print)
	RFID add-on module
	Media Stacker

* All other Meto MR-4 and MI-4 models with display can also be operated in Stand Alone Mode.

Please contact your local Checkpoint representative for further information

Austria +43 1 6 16 2411; Belgium +32 15 287 200; Czech Republic +42 024 491 0194;
Denmark +45 44 84 1 444; Finland +35 895 123 450; France +33 1 30 47 30 47;
Germany +49 6252 7030; Hungary +36 2652 5570; Italy +39 02 90 3551;
The Netherlands +31 30 60 94 111; Norway +47 22 90 33 00; Poland +48 61 8462 300;
Portugal +35 12 19 89 7200; Slovakia +421 2 456 40 351; Spain +34 93 745 4800;
Sweden +46 850 65 66 00; Switzerland +41 1 744 58 00; UK +44 13 44 70 1 200.

www.CheckpointEurope.com

MR-4/MI-4 STAND ALONE

IPMLS-BCS/MAV/V10405

Checkpoint
METO